

In the Specification:

Please replace paragraph [013] with the following:

[013] Referring to Figs. 1, 2 and 3, a first housing or panel 10 has a section or opening 12 to be covered by a cover panel 14. A plurality of elongated slots 16, 18 and 20 are formed in panel 10 adjacent to opening 12. Referring now to Figs. 4 and 5, each slot has first and second spaced apart substantially parallel side walls 22, 24 joined together at opposite ends thereof by a pair of end walls 26, 28. From Figs. 3, 4 and 5 it is seen that panel 10 forms a plate 11 which surrounds and extends away from the opening 12. Slot side wall 24 forms an inner edge of a portion of plate 11. A portion of plate 11 adjacent to side wall 24 extends only outwardly away from the slots 16 - 20 and extends generally perpendicularly to a surface of side wall 24.

Please replace paragraph [019] with the following:

[019] Each latch 34, 36 and 38 thus performs latch, tension, and release functions. The latches are located on opposite ends of the cover 14 and each defines a hinge axis about which the cover 14 can pivot so that either end of the cover 14 may be lifted. The latches on the end of the cover 14 being lifted are removed from their corresponding slots while the latches on the other end of the cover 14 remain pivotally retained within their slots. The cover 14 may also be totally removed from the housing 10 by lifting both ends of the cover 14 together to removing all the latches 34-38 from the slots 16-20. As best seen in Fig. 2, each latch 34, 36, 38, when fully inserted in the slots 16, 18 and 20, is pivotally engagable with the slot side walls 22, 24 and is pivotal with respect to the side walls 22, 24.

Delete page 10, and the "Assignment" thereon.